

1U Rackmount

Compact backup solution for rack environments

The Tandberg Data 1U Rackmount is the ideal solution for customers with limited rack space. The small footprint allows customers to consolidate external storage needs within a high-density form factor. The 1U Rackmount provides a simple and effective solution for attaching LTO, DAT and RDX drives within a rack environment.

The 1U Rack is available with SCSI, SAS and USB connectivity. The 1U Rack-USB version supports RDX and DAT drives and the 1U Rack-SCSI/SAS version supports LTO drives. The 1U Rack is compatible with old and new drive technologies, providing a compact solution for customers wishing to migrating data from older formats (DLT, AIT etc.) on to new formats (LTO and RDX).

The 1U Rackmount is fitted with dual fans to ensure that the internal devices are kept cool, improving performance and reliability. The 1U rack products are supplied with a 3-year warranty, installation manual, power supply, dual fans, power cord, quick deploy rail kit, management arm and quick release levers for easy installation of tape drives. The top access cover and removable drive trays allow customers to slide the unit out of the rack for easier access to drives.

Please note that LTO, DAT and RDX drives must be ordered separately.



Key Benefits

- === **Capacity/Performance**
Storage capacities up to 6.0TB* and speeds up to 2.0TB/hr* (LTO-5 HH)
- === **Compact Design**
High-density 1U form factor, supports up to two half-height drives
- === **Scalability**
Improve backup performance by adding a 2nd drive
- === **Flexibility**
Multiple interfaces; SCSI, SAS and USB allow for easy data migration
- === **Ease of Use**
Compact robust design allows for easy installation

* Assumes a 2:1 compression ratio



The 1U Rackmount provides a simple and effective solution for attaching LTO, DAT and RDX drives within a rack environment.

Specifications

Form Factor	1U
Max Number of Drives	2x HH Drives (LTO, DAT or RDX)
Drives Supported	LTO: LTO-2 HH, LTO-3 HH, LTO-4 HH & LTO-5 HH DAT: DDS4, DAT72, DAT160 & DAT320 RDX: RDX (USB)
External Interface	SCSI: 2x 68-pin HD SAS: 2x mini-SAS 8088 connectors USB: 2x Std. A-type connectors
Internal Interface	SCSI: 2x 68-pin HD (Includes internal termination) SAS: 2x mini-SAS 8042 connectors USB: 2x Std. B-type connectors
Power Specifications	140 Watts, max 100 to 240 Vrms Nominal Line Voltage

Dimensions

Physical (HxWxD)	1.7 x 19 x 25.3 in (4.32 x 42.88 x 64.14 cm)
Shipping (HxWxD)	12.0 x 23.5 x 33.5 in (30.48 x 59.69 x 85.09 cm)
Weight Out of Box	17.8 lb (8.07 kg)
Weight Shipping	25 lb (11.3 kg)

Environmental Specifications

Temperature (Operating)	41° to 104° F (5° to 40° C)
Temperature (Storage)	-22° to 104° F (-30° to 60° C)
Relative Humidity (Operating)	20% to 80%
Relative Humidity (Non-operating)	5% to 95%
Warranty	3yrs, 1yr ARS

* Assumes a 2:1 compression ratio

About Tandberg Data

Tandberg Data is a leading global supplier of data protection solutions for small and medium-sized businesses. The company's wide range of cost-effective storage products and services provides customers with best-in-class tape, disk, removable disk and software solutions for backup, archiving and disaster recovery. These solutions are marketed through a global channel of qualified resellers, distributors and major server OEMs. An extensive service and support network supports all Tandberg Data products worldwide.

DS-1URackmount_A4_2011A

Tandberg Data GmbH
Feldstrasse 81
44141 Dortmund
Germany
Tel: 00 800 8263 2374 (00 800 TANDBERG)
Fax: +49 (0) 231 5436 - 111
salesemea@tandbergdata.com
www.tandbergdata.com/emea

Tandberg Data Corporation
10225 Westmoor Dr., Ste. 125
Westminster, CO 80021
USA
Tel: (800) 392-2983 Toll Free
Fax: 303.417.7170
sales@tandbergdata.com
www.tandbergdata.com/us

Tandberg Data (Asia) Pte. Ltd
7 Tai Seng Drive
#02-00
Singapore 535218
Tel: +65 6593 4700
Fax: +65 6281 7358
salesapac@tandbergdata.com
www.tandbergdata.com/apac

Tandberg Data (Japan) Inc.
Dai 6 Ito Building 5F,
4-4-7 Ebisu, Shibuya-ku,
Tokyo, 150-0013
Tel: +81 3 5475 2140
Fax: +81 3 5475 2144
TDJ_sales@tandbergdata.com
www.tandbergdata.com/jp