

Standalone Backup Products

RDX

Drive Type	Capacity	Transfer Rate	Interface	Warranty
RDX	160GB, 320GB, 500GB, 640GB, and 1TB	25MB/s (USB) 45MB/s (SATA)	USB-2 (External) SATA & USB-2 (Internal)	3-years ARS [‡]



POSITIONING AND FEATURES

Entry-level removable disk-based backup solution, designed for SMBs.	Ease of use, easy to install, multi-function e.g. drag & drop.
Supplied with AccuGuard™ Backup and Recovery Software.	Environmentally friendly and low power consumption.
Combines the simplicity of tape with the speed and flexibility of a hard drive.	High quality shockproof cartridges (10,000 uses / 10 years).

DAT

Drive Type	Capacity	Transfer Rate	Interface	Warranty
DAT72	36GB / 72GB*	24.3GB/hr*	SCSI LVD, USB-2	3-years, 1st year ARS [‡]
DAT160	80GB / 160GB*	49.0GB/hr*	SCSI LVD, USB-2	
DAT320	160GB / 320GB*	86.4 GB/hr*	SAS, USB-2	



POSITIONING AND FEATURES

Entry-level tape backup solution, designed for SMBs.	Future-proof 8-generation roadmap.
The most successful tape drive ever, 16 million drives sold to date.	Protect your offsite data with AES 256-bit encryption (DAT320 only).
Easy of use, out of box to backup in less than 1 minute.	Environmentally friendly and low power consumption.
Low media cost and One Button Disaster Recovery (OBDR).	

LTO

Drive Type	Capacity	Transfer Rate	Interface	Warranty
LTO-2 HH	200GB / 400GB*	173GB/hr*	SCSI LVD	3-years ARS [‡]
LTO-3 HH	400GB / 800GB*	432GB/hr*	SCSI LVD	
LTO-4 HH	800GB / 1.6TB*	576GB/hr*	SCSI LVD, SAS	
LTO-5 HH	1.5TB / 3.0TB*	1.0TB/hr*	SAS, FC	
LTO-4 FH	800GB / 1.6TB*	864GB/hr*	SCSI LVD, SAS, FC	
LTO-5 FH	1.5TB / 3.0TB*	1.0TB/hr*	SAS, FC	



POSITIONING AND FEATURES

Midrange tape backup solution, designed for SMBs.	LTO tape technology provides peace of mind and choice.
Provides customers with high capacity and maximum performance and reliability.	Multiple configurations: Internal, external and rackmount.
Drive capacities from 200GB (native) to 1.5TB (native).	Multiple interfaces: SCSI, SAS and FC.
Drive performance from 12MB/s (native) to 140MB/s (native).	Future-proof 8-generation roadmap
Offers customers the lowest TCO for long-term storage (LTO-4 <\$0.02/GB).	

* Native / Compressed. Assumes a 2:1 compression ratio. Compression capacity and throughput will vary dependent upon the type of data and the system configuration.
[‡]ARS = Advanced Replacement Service. Product warranty may be subject to change in some regions. Please contact Tandberg Data for more information.

CH-DriveMatrix_EN_2010B

Tandberg Data GmbH
Feldstrasse 81
44141 Dortmund
Germany
Tel: +49 (0) 231 5436 - 0
Fax: +49 (0) 231 5436 - 111
00 800 8263 2374 (00 800 TANDBERG)
salesemea@tandbergdata.com
www.tandbergdata.com/emea

Tandberg Data Corporation
10225 Westmoor Dr., Ste. 125
Westminster, CO 80021
USA
Tel: 303.442.4333
Fax: 303.417.7170
Toll Free: (800) 392-2983
sales@tandbergdata.com
www.tandbergdata.com/us

Tandberg Data (Japan) Inc.
Dai 6 Ito Building 5F,
4-4-7 Ebisu, Shibuya-ku,
Tokyo, 150-0013
Tel: +81 3 5475 2140
Fax: +81 3 5475 2144
tdj_sales@tandbergdata.com
www.tandbergdata.com/jp

Tandberg Data (Asia) Pte. Ltd
7 Tai Seng Drive
#02-00
Singapore 535218
Tel: +65 6593 4700
Fax: +65 6281 7358
salesapac@tandbergdata.com
www.tandbergdata.com/apac