

## RDX® QuikStor™

*Rugged, Reliable and Removable  
Storage for your Business*

The Tandberg Data RDX QuikStor media-based removable storage system offers rugged, reliable and convenient storage for backup, archive, data interchange and disaster recovery. It provides enterprise performance and fast access, with transfer rates up to 260 MB/s and is available with up to 3TB per cartridge.

### Enterprise Reliability

The exploding growth of mission-critical digital content combined with government regulated retention policies has created a need for secure, reliable and portable data protection solutions at an affordable cost. The Tandberg Data RDX QuikStor technology delivers a rugged design for maximum data protection and secure handling. Full backward/forward compatibility allows users to scale to higher capacities, without worrying about drive generations.

### High Performance

SuperSpeed USB 3.0 interface offers high performance. With a choice of hard disk and solid-state disk media, unique performance requirements are met. From professional workstations to the low-end enterprise, RDX QuikStor provides users with best-in-class backup and archive capability that is ideally suited to help users get their businesses up and running quickly in the event of data loss.

### External USB3+ Version for more mobility

The external RDX USB3+ drive only needs a USB3.0 connection to work. It is as easy to use as an external USB disk drive but much more robust and reliable. This enables RDX for outdoor usage like scientific data collection, in the media and entertainment environment, mobile workforce or just for easy data distribution across locations.

### Fixed Disk Mode for Windows® Backup

Windows-Backup of current operating systems does not support removable media any more. Users are constrained either to refrain from an operating system upgrade, or to use a third party backup software. RDX QuikStor provides a fixed disk mode in USB3.0 and USB3+ drives and allows a seamless integration into Windows-backup utility.

### Capacity Expansion and Media Rotation

Media Spanning to multiple RDX media allows backups to grow and to expand capacity beyond a single RDX media. All that is needed: Multiple RDX media and supporting backup software. For best practice, multiple media should be used for backup and stored off-site for disaster recovery purposes. A minimum rotation of 3 media is recommended: 1<sup>st</sup> in drive for next backup, 2<sup>nd</sup> in transit and 3<sup>rd</sup> off-site for disaster recovery.

### Additional Protection

RDX WORM enhances RDX for compliant archiving (optional software solution). RDX Cartridge Encryptor (RCE) is free software to encrypt data stored on RDX media.

Now available:  
External USB3+  
Version



**rdx**  
QUIKSTOR™

## Key Benefits

- ▬ **Fast Access**  
Disk-based speed and data-access
- ▬ **Budget-Friendly**  
Cost-effective solution that suits all sectors from SOHO users to departmental users
- ▬ **Flexible**  
USB3.0 SuperSpeed and SATA interface, internal and external drives, SSD and HDD media in different capacities
- ▬ **Rugged and Tough**  
Rugged, shock and electrostatic proof media with more than 10 years archive life
- ▬ **Convenient & Secure**  
Expand capacity and span backups across media. Media rotation and off-site copies for archiving and peace of mind
- ▬ **Mobile**  
The external USB3+ version can be used as a mobile storage device
- ▬ **19"-Rack Integration with QuadPAK™**  
Up to 4 external RDX USB drives can be easily installed in a 19"-rack
- ▬ **Windows-Backup support**  
Configurable operating mode for Windows Backup Application in all USB3.0 versions
- ▬ **AccuGuard™ for RDX QuikStor**  
Provides "set it and forget it" data protection with 20:1\* data deduplication

\* Typical



Choose between 500GB, 1TB, 2TB or 3TB HDD media or 128GB, 256GB or 512GB SSD media. The backward/forward compatibility allows users to upgrade to higher capacity media without compromise.



TANDBERG DATA

Specifications					
	Internal RDX Drives			External RDX Drives	
Form Factor	3.5" (SATA/USB3.0)	5.25" (SATA/USB3.0)		External Housing (USB3.0)	
Height	41 mm (1.63 in)	41 mm (1.63 in)		52 mm (2.04 in)	
Width	102 mm (4.00 in)	146 mm (5.78 in)		110 mm (4.32 in)	
Length	159 mm (6.28 in) incl. bezel	170.72 mm (6.72 in) incl. bezel		178 mm (7.00 in) incl. bezel	
Weight	408 g (0.9 lb)	635 g (1.4 lb)		615 g (1.35 lb)	
Mounting & Operating Orientation	Horizontal or Vertical				
Interface	SATA I	USB3.0		USB3.0	USB3.0 (USB powered)
Interface Connector	SATA	Type-B		Type-B	
Interface Operation Mode	Removable Disk	Removable Disk & Fixed Disk		Removable Disk & Fixed Disk	
Transfer Rate Average Sustained	Up to 45 MB/s	Up to 260 MB/s		Up to 260 MB/s	
File Access Time (average)	< 15 milliseconds				
<b>Power Specifications</b>					
Voltage	+5 V	+5 V	+12 V	+12 V	+5 V (USB powered)
Current at Read/Write (Typical / Peak)	0.9 A / 1.6 A	0.9 A / 1.6 A	0.005 mA / 1.4 A	0.5 A / 1 A	0.9 A / 1.6 A
Power Connector	SATA Power	4-Pin Molex		5.5 mm	optional: 5.5 mm
Power Adapter	4-Pin Molex to SATA Power	SATA Power to 4-Pin Molex	Wall Adapter:	+12 V (+/-10%), 1.0 A	optional Wall Adapters: +5 V (+/- 10%) 2.4 A to +12 V (+/- 10%) 1.0 A
<b>Media</b>					
Capacity	500GB, 1TB, 2TB or 3TB (HDD) / 128GB, 256GB or 512GB (SSD) <i>See RDX Media datasheet for more information</i>				
Read/Write Compatibility	Forward/backward compatibility to all RDX drives and systems				
<b>Reliability</b>					
Media Drop Shock (Non-operating)	1m drop to tile over concrete floor (Media)				
Load-/ Unload (Minimum)	Drive: 10,000 insertion / removal cycles, Media: 5,000 insertion / removal cycles				
MTBF	550,000 Hours				
Vibration (max)	0.5G (operating), 1.0G (non-operating)				
<b>Environmental</b>					
Temperature	+10°C to +40°C (+50°F to +104°F) (operating), -40°C to +65°C (-40°F to +149°F) (non-operating)				
Relative Humidity	20% – 80% (non-condensing, operating), 8% – 90% (non-condensing, non-operating)				
Altitude	-15 m to 3,048 m (-50 ft to 10,000 ft) (operating), -15 m to 10,660 m (-50 ft to 35,000 ft) (non-operating)				
<b>Other Features</b>					
Encryption	Supports software-based encryption				
WORM	Enables compliant Archiving with rdxLOCK WORM Software				
Compression and Deduplication	Supports software-based compression and deduplication				
Windows Backup	Fixed Disk Mode for Windows Backup Utility available in all USB3.0 versions				
AccuGuard for RDX Backup Software	Single Server or Enterprise Backup incl. Exchange & SQL backup with deduplication				
QuikStation	iSCSI based disk array with 8 drives				

DS-RDX\_A4\_2016A

Overland Storage  
125 S. Market Street  
San Jose, CA 95113  
USA  
Tel: (858) 571-5555  
Fax: (858) 571-3664  
sales@overlandstorage.com  
www.overlandstorage.com

Tandberg Data EMEA  
Feldstrasse 81  
44141 Dortmund  
Germany  
Tel: +49 231 5436 - 0  
Fax: +49 231 5436 - 111  
sales@tandbergdata.com  
www.tandbergdata.com/de

Overland Storage UK  
Regus Atlantic House, Imperial Way  
Reading, RG2 0TD  
United Kingdom  
Tel: +44 1 189 898 000  
sales@tandbergdata.com  
www.tandbergdata.com/emea

Overland Storage France  
18 Rue Jean Rostand  
Orsay  
91400, France  
Tel: +33 1 81 91 73 40  
sales@tandbergdata.com  
www.tandbergdata.com/emea

Tandberg Data APAC  
16 Collyer Quay  
Level 21  
Singapore, 049318  
Tel: +65 6818 9266  
sales@tandbergdata.com  
www.tandbergdata.com/apac