

RDX Compatibility Guide

Revision: 1.2.5.
September 25, 2014



Backup Software Compatibility

RDX products from Tandberg Data are supported by the backup applications listed below (please click on company name for compatibility-list):

Company	Product	Notes
Acronis	Backup & Recovery	
Archiware	PresStore	
Atempo	Time Navigator	
BakBone	NetVault	
CA	Arcserve	
CA	Arcserve D2D	
CommVault	Shimpana	
EMC	Retrospect	
EMC	Networker	
HP	Data Protector	
IBM	Tivoli Storage Manager	
Microsoft	Windows NT Backup	1
Microsoft	Windows Server Backup Utility	3, 4, 5
Open Source	Tar	2
Paragon	Hard Disk Manager	
Paragon	Protect & Restore	
SEP	Sesam	
StorageCraft	Shadow Protect	
Symantec	Backup Exec	
Symantec	Backup Exec System Recovery	
Tandberg Data	AccuGuard	
Veeam	Backup & Replication	
Yosemite	Tapeware	

Notes:

1. A hotfix is available from Microsoft that allows NT Backup on Windows Server 2003 to support spanning across RDX cartridges. See Microsoft KB article 932059.
2. For spanning across RDX cartridges use the tar -M -L size option (where size is the cartridge capacity in kilobytes) when creating multiple-volume backups. For more information, refer to the main page for tar.
3. The Microsoft native backup utility from Server 2008 R2 should be used with RDX Fixed Disk Mode.
4. For Windows Server 2012 Hotfix KB xxx is required
5. Works only with USB 3.0 Drives

Operating System Compatibility

RDX products are compatible with the following operating systems:

Operating System		Notes
Windows XP	Home and Professional	
Windows Vista SP1	32 & 64 Bit Business Editions	
Windows 7	32 bit & 64 bit	2
Windows 8		
Windows 8.1		
Windows Server 2003	32 bit & 64 bit, all Editions	1
Windows Server 2003 R2	32 bit & 64 bit, all Editions	
Windows Server 2008	32 bit & 64 bit, all Editions	2
Windows Server 2008 R2	32 bit & 64 bit, all Editions	
Small Business Server 2008		
Small Business Server 2011		
Windows Server 2012	All Editions	
Windows Server 2012 R2	All Editions	4
MacOS	OS X 10.4 and later	
CentOS Linux	Version 4.2, kernel version 2.6.9 and later	
Fedora Core 5	Kernel version 2.6 and later	
RHEL	RHEL 3.0 Update 7 and later	
SLES	SLES 9 Service Pack 3 and later	3
Solaris	Version 10 1/13, Version 11.1	

Notes:

1. Small Business Edition backup wizard does not allow the user to select the RDX or any other removable drive as the backup target. Use RDX fixed disk mode.
2. There are limitations with the native backup application, use RDX fixed disk mode.
3. SLES 9 Service Pack 3 does not support SATA ATAPI devices and therefore does not support the RDX Internal SATA device.

File System Compatibility

In principle the RDX cartridge can be formatted for any file system. The following file systems have been tested by Tandberg Data:

File System	OS (s)	Notes
FAT32	Windows XP Windows Vista SP1 Windows Server 2003 Windows Server 2003 R2 Windows Server 2008 Windows Server 2008 R2	<ul style="list-style-type: none"> • Max file size = 4GB • Windows does not allow user to reformat cartridge as FAT32 • Windows Explorer may not display volume label the first time a cartridge is inserted
NTFS	Windows XP Windows XP Pro Windows Vista SP1 Windows 7 Windows 8, 8.1 Windows Server 2003 Windows Server 2003 R2 Windows Server 2008 Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 R2	
exFAT	Windows 7 Windows 8, 8.1 Windows Server 2008 Windows Server 2008 R2 Windows Server 2012 Windows Server 2012 R2	
ext2	Linux	
ext3	Linux	
ext4	Linux	
Mac OS Extended	Mac OS HPFS	

SATA Host Bus Adapter Compatibility

Tandberg Data has tested the internal SATA RDX dock against the SATA Host Bus Adapters listed below:

HBA or Motherboard	Notes
Intel ICH6	
Intel ICH6R	
Intel ICH7	
Intel ICH7R	
Intel ICH8R	
Intel ICH9R	
Intel ESB2	
Silicon Image 3112	1, 2, 3
Silicon Image 3114	1
Silicon Image 3124	1, 2, 3
Intel S3000AHV Motherboard	non-RAID or Matrix RAID modes - 4
Promise SATA300 TX4 4-port	5, 7,8 (not a recommended configuration)
Promise TX300	5, 7,8 (not a recommended configuration)
Broadcom HT1000	6

Notes:

1. Silicon Image HBA's may require updated BIOS and drivers to work with SATA ATAPI devices.
2. Can only format the cartridge using the "quick format" option under Windows.
3. Windows Check Disk utility does not operate correctly.
4. Does not work in Intel Embedded Server RAID mode.
5. Eject button does not operate correctly.
6. May require a driver update from Broadcom in order to operate in QDMA mode.
7. Write protected cartridges cannot be read on Windows hosts due to a limitation of the Promise driver . The issue has not been tested on Linux systems.
8. Use of Promise SATA add-in card with button eject requires RDX host tools release 1.33 or later and registry key workaround value

HKEY_CURRENT_CONFIG\SYSTEM\CurrentControlSet\Services\RDXmon\
Configuration\ScsiMediaDetection

to be set. Setting this registry key may keep the cartridge volume label from being detected in some cases.

USB Compatibility

The USB RDX drives work with all USB controllers. Tandberg Data has tested the USB RDX drives against the USB controller types listed below (using specific controllers from most major USB controller manufacturers):

Host Controller Types		Notes
EHCI (2.0)	Enhanced Host Controller Interface	
UHCI (1.1)	Universal Host Controller Interface	
OHCI (1.1)	Open Host Controller Interface	

The USB RDX drive is compatible with the USB Mass Storage Specification for Bootability 1.0.

The USB RDX drives are certified to meet the USB-IF High Speed Compliance Standards for USB2.0 and USB3.0.

The following USB 3.0 PCIe HBAs are certified (NEC / Renesas Chipset):

Akasa AK-PCCK 3-02
DeLock 89243 PCIe

Eject Button Support

Windows

Windows does not have native support for removable disk drives. Specifically, the operating system does not allow the eject button to operate with cartridges formatted with the NTFS file system. It does allow the user to eject the cartridge using Windows Explorer (right-click on drive letter, select “Eject”).

Tandberg Data supplies a utility that allows the eject button to operate properly on Windows. This utility runs as a Windows service. See the RDX Utility Users Guide for installation instructions.

Linux/Mac OS X/Solaris

Linux, Solaris and Mac OS X do not typically support the eject button operation. Use the recommended system method to eject the removable media.